

## SyntiSOL PP Heavy 260

### ■ satin 3393 - 260 µm

Thick and solid PP film for increased stability and stiffness. The product is fully waterproof and extremely scratch resistant. The solvent coating allows short drying time, high saturation and brilliant photo quality printing. The product is very well suitable for indoor and outdoor applications such as POS, displays or even economic high quality photo applications.

#### Applications

- Vibrant photo-realistic image reproduction
- Indoor signs
- Indoor short-term promotions
- PoP-up Displays
- Outdoor signage
- Billboard, advertising

#### Advantages

- High stability and stiffness
- Suitable for eco- and true-solvent inks
- High color brilliance
- Short drying time
- Scratch and waterproof

## SyntiSOL PP Heavy 260

■ satin 3393 - 260 µm

### List of Printers

Printer	Ink	Quality
Hewlett Packard DJ 8000S / 9000S / 10000S	Eco Solvent	Excellent
Hewlett Packard DJ L65500 Latex ink	IR Curing / Latex Ink	Excellent
Hewlett Packard DJ L25500 Latex ink	IR Curing / Latex Ink	Excellent
Hewlett Packard Scitex LX 600	IR Curing / Latex Ink	Excellent
Hewlett Packard Scitex LX 800	IR Curing / Latex Ink	Excellent
ColorSpan DisplayMaker 72S	Eco Solvent	Good
Epson Stylus Pro GS6000 UltraChrome GS	Eco Solvent	Excellent
Roland SolJet SJ540 / SC540 SJ 740 / SC740	Eco Solvent	Excellent
Roland SC-500 Permasol S	Solvent Ink	Good
Roland VersaCAMM SP-300i / SP-540i	Eco Solvent	Excellent
Roland VS 540 / VS 640	Eco Solvent	Excellent
Mimaki JV-3 160S, 250	Solvent Ink	Good
Mimaki JV 5-130 / -160	Eco Solvent	Good
Mimaki JV 33	Eco Solvent	Excellent
Mutoh Rockhopper 46", 62"	Eco Solvent	Good
Mutoh Rockhopper II 50", 64", 87"	Eco Solvent	Good
Océ CS6060	Eco Solvent	Excellent
Seiko SII Colorpainter 64S / 100S	Eco Solvent	Excellent

Last update: 11.03.2011

## SyntiSOL PP Heavy 260

■ satin 3393 - 260 µm

### Physical Properties

Weight	180g/m2	ISO 536
Thickness	260µm	ISO 534
Opacity	94 %	Macbeth TD-904

### Conditions of Use and Stocking

The converting and storage should take place in a climate from 35 to 65% to relative humidity at a temperature from 10 to 30°C. Keep the product in the original packaging (cardboard box and PE bag). It is always recommended that cotton gloves be used when handling InkJet coated materials to avoid fingerprints.

The data provided in this product data sheet are values for orientation only.

Before using our print media please check their suitability for your printer and for your intended application. We do not take any liability for failures or damages resulting from technically modified printing inks and/or printers as technical specifications are subject to change.

16.02.2006